

NEW
“NAUTALIFT™ STAINLESS STEEL GAS LIFT SUPPORTS”
NEW

**Marine Grade Gas Filled Supports –**  
**Designed for demanding saltwater applications**  
**316L Stainless Steel Rod and Cylinder**  
**Engineered polymer rod ends**  
**Bronze bushings**  
**Multi-lobe internal seal**



Part No.	OE No.	Extended Length (inches)	Compressed Length (inches)	Rated (pounds)
GSS62600	GSSX-4900-20	7.5	5.5	20
GSS62610	GSSX-4900-40	7.5	5.5	40
GSS62630	GSSX-5000-20	10	7	20
GSS62640	GSSX-5000-40	10	7	40
GSS62670	GSSX-5100-30	12	8.5	30
GSS62680	GSSX-5150-20	15	9.5	20
GSS62700	GSSX-5150-40	15	9.5	40
GSS62710	GSSX-5150-60	15	9.5	60
GSS62720	GSSX-5200-20	17	11	20
GSS62740	GSSX-5200-40	17	11	40
GSS62750	GSSX-5200-50	17	11	60
GSS62760	GSSX-5200-90	17	11	90
GSS62770	GSSX-5300-20	20	12	20
GSS62780	GSSX-5300-30	20	12	30
GSS62790	GSSX-5300-40	20	12	40
GSS62800	GSSX-5300-60	20	12	60
GSS62820	GSSX-2300-90	20	12	90
GSS62830	GSSX-2300-120	20	12	120



**GS62840**  
Black zinc plated steel flat bracket with 10mm ball stud. 2.25" wide.



**GS62850**  
Stainless steel flat bracket with 10mm ball stud. 2.25" wide.



**GS62860**  
Black zinc plated steel 90° angle bracket with 10mm ball stud. 2" wide, .65" base.



**GS62870**  
Stainless steel 90° angle bracket with 10mm ball stud. 2" wide, .65" base.



**GS62880**  
Black zinc plated steel 90° angle bracket with 10mm ball stud. 2" x 1.2" base.



**GS62900**  
Stainless steel 90° angle bracket with 10mm ball stud. 2" x 1.2" base.



**GS62910**  
Zinc plated steel 10mm ball stud with threaded shaft.



**GS62920**  
Stainless steel 10mm ball stud with threaded shaft.



**GS62890**  
Rod end with internal threads for either end of Nautalift gas filled lift supports. Unique construction makes installation easy and safe.

ELEG. PROD.