



SHIELDS HOSE Engine Coolant/Exhaust

SHIELDS

Improved
Now double the
ozone resistance
required by SAEJ2006




SHIELDSFLEX II MARINE WATER/EXHAUST HOSE (w/wire)

	I.D.	O.D.	Ply	Burst Pressure	Wt. "C"	50' Coil Code #	25' Cartons	12 1/2' Length Code #	6 1/4' Length Code #
• Engine Intake	1/2"	27/32"	2	870#	24	16-250-0120	16-250-0125	16-250-0124	16-250-0121
• Wet Exhaust Connections – Use Where Bends Or Long Lengths Required	5/8"	61/64"	2	725#	28	16-250-0580	16-250-0585	16-250-0584	16-250-0581
	3/4"	1 1/16"	2	630#	32	16-250-0340	16-250-0345	16-250-0344	16-250-0341
	7/8"	1 3/16"	2	565#	36	16-250-0780	16-250-0785	16-250-0784	16-250-0781
	1"	1 5/16"	2	500#	40	16-250-1000	16-250-1005	16-250-1004	16-250-1001
	1 1/8"	1 7/16"	2	465#	44	16-250-1180	16-250-1185	16-250-1184	16-250-1181
	1 1/4"	1 19/32"	2	420#	50	16-250-1140	16-250-1145	16-250-1144	16-250-1141
• Bilge Pump Intake/Discharge	1 5/16"	1 5/8"	2	400#	51	16-250-1560	–	16-250-1564	16-250-1561
	1 3/8"	1 23/32"	2	370#	58	16-250-1380	16-250-1385	16-250-1384	16-250-1381
• Scupper Lines	1 1/2"	1 53/64"	2	360#	62	16-250-1120	16-250-1125	16-250-1124	16-250-1121
• Toilet Intake, Discharge	1 5/8"	2"	2	320#	80	16-250-1580	–	16-250-1584	16-250-1581
	1 3/4"	2 1/8"	2	300#	88	16-250-1340	–	16-250-1344	16-250-1341
	1 7/8"	2 19/64"	2	275#	93	16-250-1780	–	16-250-1784	16-250-1781
• Holding Tank Vent, Pump Out	2"	2 13/32"	2	260#	99	16-250-2000	–	16-250-2004	16-250-2001
	2 1/8"	2 17/32"	2	245#	107	16-250-2180	–	16-250-2184	16-250-2181
	2 1/4"	2 11/16"	2	230#	127	16-250-2140	–	16-250-2144	16-250-2141
Black synthetic rubber tube and cover.	2 3/8"	2 3/4"	2	230#	132	16-250-2380	–	16-250-2384	16-250-2381
Reinforced with wire helix imbedded between plies of HD synthetic cord.	2 1/2"	2 7/8"	2	220#	137	16-250-2120	–	16-250-2124	16-250-2121
	2 5/8"	3 1/16"	2	200#	147	16-250-2580	–	16-250-2584	16-250-2581
	2 3/4"	3 3/16"	2	200#	164	16-250-2340	–	16-250-2344	16-250-2341
	2 7/8"	3 5/16"	2	190#	170	16-250-2780	–	16-250-2784	16-250-2781
Resistant to: exhaust fumes, ozone, mild chemicals, antifreeze, salt water. Abrasion resistant. Odor permeation resistant.	3"	3 7/16"	2	190#	177	16-250-3000	–	16-250-3004	16-250-3001
	3 1/8"	3 5/8"	2	175#	200	16-250-3180	–	16-250-3184	16-250-3181
	3 1/4"	3 45/64"	2	175#	208	16-250-3140	–	16-250-3144	16-250-3141
	3 1/2"	4"	2	160#	223	16-250-3120	–	16-250-3124	16-250-3121
	4"	4 5/8"	2	130#	269	16-250-4000	–	16-250-4004	16-250-4001
	4 1/8"	4 47/64"	2	130#	276	16-250-4180	–	16-250-4184	16-250-4181
	4 1/2"	5 3/32"	2	120#	319	16-250-4120	–	16-250-4124	16-250-4121
Temperature range: -20° to +200° F continuous, +250° intermittent	5"	5 5/8"	2	100#	398	16-250-5000	–	16-250-5004	16-250-5001
	5 1/8"	5 3/4"	2	150#	417	16-250-5180	–	16-250-5184	16-250-5181
	5 1/2"	6 3/16"	2	150#	443	16-250-5120	–	16-250-5124	16-250-5121
	6"	6 21/32"	2	130#	482	16-250-6000	–	16-250-6004	16-250-6001
	8"	8 25/32"	2	145#	780	–	–	16-250-8004	–

Meets SAE J2006
Type R2

SHIELDS VERSAFLEX™



	I.D.	O.D.	Ply	Burst Pressure	Wt. "C"	50' Coil Code #	12 1/2' Length Code #
• Engine Intake	1/2"	53/64"	2	390#	20	16-210-0120	16-210-0124
• Wet Exhaust Connections – Use Where Bends Or Long Lengths Required	5/8"	15/16"	2	330#	23	16-210-0580	16-210-0584
	3/4"	1 1/16"	2	290#	27	16-210-0340	16-210-0344
• Bilge Pump Intake/Discharge	7/8"	1 3/16"	2	260#	30	16-210-0780	16-210-0784
• Scupper Lines	1"	1 19/64"	2	200#	34	16-210-1000	16-210-1004
	1 1/8"	1 27/64"	2	200#	38	16-210-1180	16-210-1184
	1 1/4"	1 9/16"	2	180#	42	16-210-1140	16-210-1144
Black synthetic rubber tube and cover. Reinforced with wire helix imbedded between plies of synthetic cord.	1 5/16"	1 5/8"	2	175#	48	16-210-1560	16-210-1564
	1 3/8"	1 11/16"	2	170#	54	16-210-1380	16-210-1384
Resistant to: exhaust fumes, ozone, mild chemicals, antifreeze, salt water. Abrasion resistant.	1 1/2"	1 13/16"	2	150#	57	16-210-1120	16-210-1124
	1 5/8"	2"	2	145#	68	16-210-1580	16-210-1584
	1 3/4"	2 1/8"	2	140#	72	16-210-1340	16-210-1344
	1 7/8"	2 1/4"	2	130#	76	16-210-1780	16-210-1784
Temperature range: -20° to +200° F continuous, +250° intermittent	2"	2 23/64"	2	110#	90	16-210-2000	16-210-2004
	2 3/8"	2 3/4"	2	100#	129	16-210-2380	16-210-2384
	2 1/2"	2 7/8"	2	100#	135	16-210-2120	16-210-2124
	2 5/8"	3 1/8"	2	80#	160	16-210-2580	16-210-2584
Meets SAE J2006 Type R2	3"	3 15/32"	2	80#	183	16-210-3000	16-210-3004